

SUPRACO 1045

Neat Cutting Oil

NEAT - LOW EP**DESCRIPTION**

SUPRACO 1045 is a neat cutting oil specially developed for the general machining of ferrous and non-ferrous metals, it can be also used in hydraulic systems of machine-tools.

SUPRACO 1045 is recommended and widely used in the automotive and mechanical industries for turning operations on brass and mild steels.

BÉNÉFICES

- Compatible with all metals
- Optimum lubricating and anti-wear properties
- Can be used in centralised system or in individual machine
- Compatible with all kinds of filtration systems
- Reduced product consumption
- Easy removal of SUPRACO 1045 with standard washing procedures

PERFORMANCES

SUPRACO 1045 is a neat cutting oil designed for standard machining of ferrous and non-ferrous metals.

SUPRACO 1045 is particularly suited to the standard machining operations of brass and mild steels.

TECHNICAL INFORMATION

NAME	METHOD	SUPRACO 1045
Couleur	Visuel	Jaune Clair
Aspect		Transparent
Densité à 20°C (68°F)	ISO 12.185	0.880 kg/L
Viscosité à 40°C (104°F)	ASTM D445	45,0 mm ² /s
Point éclair	ASTM D92	230,0 °C
Point d'écoulement	ASTM D97	-30,0 °C
Copper Stripe Corrosion	NTF M 07105	1A
Storage		in frost-free, dry place

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com