

## SUPRACO 3020

Neat Cutting Oil

## NEAT - HIGH EP

### DESCRIPTION

**SUPRACO 3020** is a high performance neat cutting oil specially developed for machining of bad machinability ferrous metal.

**SUPRACO 3020** is widely used in the automotive and aeronautic industries.

### BÉNÉFICES

- Wide range of applications
- High lubricating and Extreme Pressure properties
- User safety (no labeling) and machine safety (high flash point)
- Can be used for both cutting and machine-tool lubrication

### SÉCURITÉ

- Free from organo-chlorinated additives
- Good dermatologic behavior for a better comfort of users
- Use of SUPRACO 3020 is not advised for machining of non-ferrous metals

### PERFORMANCES

**SUPRACO 3020** is especially suitable for machining of medium-hard to hard steel and titanium on automatic and semi-automatic turning machines, with single or multiple broaches, without risks of seizing the spindle mechanism.

**SUPRACO 3020** is specially adapted for use at a high rate under heavy use.

## TECHNICAL INFORMATION

NAME	METHOD	SUPRACO 3020
Couleur	Visuel	Jaune Clair
Aspect		Transparent
Densité à 20°C (68°F)	ISO 12.185	0.876 kg/L
Viscosité à 40°C (104°F)	ASTM D445	25,0 mm <sup>2</sup> /s
Point éclair	ASTM D92	194,0 °C
Point d'écoulement	ASTM D97	-12,0 °C
Copper Stripe Corrosion	NTF M 07105	4C
Storage		in frost-free, dry place

## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

## RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at [www.motul.com](http://www.motul.com)