



MOTULTECH SUPRACO 4030

Neat Cutting Oil

DESCRIPTION

SUPRACO 4030 is a high performance neat cutting oil designed for machining of bad machinability ferrous metals.

APPLICATIONS

SUPRACO 4030 has been developed for severe machining operations.

SUPRACO 4030 is made for difficult machining operations and grinding while being used for machine-tool lubrication.

SUPRACO 4030 is suitable for titanium, Inconel and hard materials machining operations and especially for drilling, deep reaming, tapping and grinding.

ADVANTAGES

- High Extreme Pressure properties.
- High flash point.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACO 4030
Color	-	ASTM D1500	2
Density	-		0,879
Flash point	°C		
Flash point	°C	ASTM D92	209.0

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free of organo-chlorinated additives and active sulphur
- No labeling according to CLP regulation
- Storage in a frost-free and dry place

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.