



# MOTULTECH SUPRACO 4040

Neat Cutting Oil

## DESCRIPTION

**SUPRACO 4040** is a high performance neat cutting oil designed for machining operations of bas machinability ferrous metals.

**SUPRACO 4040** is compatible with all metals and can be used on non-ferrous metals.

## APPLICATIONS

### TYPES OF OPERATIONS

- Covers all areas of application (cutting, drilling, boring, reaming, threading, tapping, bar turning)

### TYPES OF MATERIALS

- All ferrous metals from mild steel to stainless steel, refractory and special as well as non-ferrous metals

### ADVANTAGES

- High Extreme Pressure properties.
- High flash point.
- Can be used for machining operations and machine-tool lubrication.
- Easily cleanable with conventional washing processes.

## TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACO 4040
Aspect	-		Transparent
Color	-	ASTM D1500	2,5
Density	-		0,884
Flash point	°C		
Flash point	°C	ASTM D92	214.0
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

## HEALTH AND SAFETY

- Free from organo-chlorinated additives
- No labeling according to CLP European regulation



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.