

**MOTULTECH SUPRACO ELECTRIC 40****A**

Deformation

DESCRIPTION

SUPRACO ELECTRIC 40 A is a smooth, neat oil with a low freezing point and excellent anti-corrosion properties.

APPLICATIONS

SUPRACO ELECTRIC 40 A is a neat oil used for the impregnation of induction core contactors, circuit breakers and other similar devices.

Impregnation of core induction sheets of contactors, circuit breakers and blanking of silicon (200 HBrinell).

ADVANTAGES

- Deformations of induction metal sheets due to repeated shocks are reduced.
- **SUPRACO ELECTRIC 40 A** can be used for degreasing and impregnation before assembly.
- Low consumption (50 mg per contactor).
- It is not sensitive to humidity and prevents scrubbing and oxidation.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACO ELECTRIC 40 A
Aspect	-		Transparent
Flash point	°C	ASTM D92	
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.