

SUPRACUT 30 K

Neat Cutting Oil

DESCRIPTION

SUPRACUT 30 K is a dark neat oil, designed for threading operations by knurling deformation of mild steels and high alloyed steels.

APPLICATIONS

SUPRACUT 30 K is especially suitable for knurling operations to realise a threading with various sizes wheels on all types of steels, from the mildest one to stainless steel and highly alloyed steels on machines such as **PEE WEE - ESCOFIER - GROS**.

In some cases, there can be a risk of staining on non-ferrous metals by using **SUPRACUT 30 K**.

ADVANTAGES

- High lubricating power.
- Good extreme-pressure properties.
- High flash point.
- Good wettability.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACUT 30 K
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behavior

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.