

(PREVIOUSLY SUPRACO 556 SB)

SUPRACUT 30 K

Neat Cutting Oil

DESCRIPTION

SUPRACUT 30 K is a dark neat oil, designed for threading operations by knurling deformation of mild steels and high alloyed steels.

APPLICATIONS

SUPRACUT 30 K is especially suitable for knurling operations to realise a threading with various sizes wheels on all types of steels, from the mildest one to stainless steel and highly alloyed steels on machines such as **PEE WEE - ESCOFIER - GROS**.

In some cases, there can be a risk of staining on non-ferrous metals by using **SUPRACUT 30 K**.

ADVANTAGES

- High lubricating power.
- Good extreme-pressure properties.
- High flash point.
- Good wettability.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACUT 30 K
Color	-		Black
Density	-	ASTM D4052	0.873
Viscosity at 40°C	-	ASTM D445	32.2
Flash point	-	ASTM D92	220
Copper corrosion	-	ASTM D130	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behavior



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.