



## MOTULTECH SUPRACUT 40 B

Neat Cutting Oil

### DESCRIPTION

**SUPRACUT 40 B** is a chlorine free neat cutting oil specially designed for severe machining operations on ferrous and very hard metals.

### APPLICATIONS

**SUPRACUT 40 B** is suitable for all machining operations, and specially for severe operations like broaching, gear cutting, deep drilling and tapping on high alloyed steels, nickel alloys and titanium. It can be used to replace chlorinated products.

Its use is not advised for machining of copper alloys.

### ADVANTAGES

- High lubricating power.
- Very good extreme-pressure properties.
- Increase the tool life.
- High flash point.
- Reduce waste treatment compared to chlorinated oils.

### TECHNICAL INFORMATION

| TECHNICAL CHARACTERISTICS | UNITS | METHOD | SUPRACUT 40 B            |
|---------------------------|-------|--------|--------------------------|
| Aspect                    | -     |        | Transparent              |
| Storage                   | -     |        | in frost-free, dry place |

These characteristics are given only for information and can be updated over time.

### HEALTH AND SAFETY

- Free of organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behaviour

### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



#### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.