

MOTULTECH SUPRACUT 50 B

Neat Cutting Oil

MINERAL BASE

DESCRIPTION

SUPRACUT 50 B is a chlorine free neat cutting oil specially designed for severe machining operations on ferrous and very hard metals.

APPLICATIONS

SUPRACUT 50 B is suitable for all machining operations, and specially for severe operations like broaching, gear cutting, deep drilling and tapping on high alloyed steels, nickel alloys and titanium.

It can be used to replace chlorinated products.

Its use is not advised for machining of copper alloys.

SUPRACUT 50 B can also be used for deep drawing deformations, rolling and for all operations involving manual lubrication.

SUPRACUT 50 B can be used as an extreme-pressure booster additive for all other SUPRACUT series.

ADVANTAGES

- High lubricating power.
- Very good extreme-pressure properties.
- Increase the tool life.
- High flash point.
- Reduce waste treatment compared to chlorinated oils.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACUT 50 B
Aspect	-		Transparent
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.