



MOTULTECH SUPRACUT EVO 20 M

METAL TURNING OIL

DESCRIPTION

SUPRACUT EVO 20 M is a chlorine and sulphur-free neat cutting oil designed for general machining operations of all types of metals and in all types of machines.

APPLICATIONS

SUPRACUT EVO M is a range of neat cutting oils designed for all standard turning operations of hard materials (steel, titanium and inconel), non-ferrous metals and mild steels.

SUPRACUT EVO 20 M reduces significantly the cutting force which results in very neat surfaces and it is hence also perfect for cutting operations with very small chip removal.

ADVANTAGES

- Wide range of applications.
- High viscosity index.
- Good anti-wear properties.
- High flash point.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACUT EVO 20 M
Aspect	-		Clear
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free of organo-chlorinated additives and active sulphur
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behavior

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.