

Supracut EVO 215

Neat Cutting Oil

NEAT - LOW EP

DESCRIPTION

SUPRACUT EVO 215 is a high performance neat cutting oil, based on highly refined base stocks. Its use brings a better comfort for workers in term of work environment, performances and HSE.

Clear and odorless, **SUPRACUT EVO 215** is specially made for standard machining operations on ferrous and non-ferrous metals.

BÉNÉFICES

- Wide range of applications
- Reinforced lubricating properties
- Good anti-wear properties
- High flash point
- High viscosity index
- Compatible with conventional cleaning procedures

SÉCURITÉ

- Free from organo-chlorinated additives
- Good dermatological behaviour

PERFORMANCES

SUPRACUT EVO 215 is a neat cutting oil designed for all standard machining operations on ferrous and non-ferrous metals.

SUPRACUT EVO 215 is particularly suitable for machining operations on aluminium, brass, copper and all types of steels.

Its use can be extended to some fine blanking operations as well as roller-burnishing.





TECHNICAL INFORMATION

NAME	METHOD	SUPRACUT EVO 215
Couleur	Visuel	Jaune
Aspect		Transparent
Densité à 20°C (68°F)	ISO 12.185	0.840 kg/L
Viscosité à 40°C (104°F)	ASTM D445	15,0 mm²/s
Point éclair	ASTM D92	192,0 °C
Point d'écoulement	ASTM D97	-24,0 °C
Copper Stripe Corrosion	NTF M 07105	1B
Storage		in frost-free, dry place

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com