



MOTULTECH SUPRACUT MQL 45

Minimum Quantity Lubrication

DESCRIPTION

SUPRACUT MQL 45 is a synthetic neat cutting oil developed for machining involving chips removal of ferrous and non-ferrous metals, with a micro-spray circulation system.

APPLICATIONS

SUPRACUT MQL is a range of synthetic neat cutting oils best suited for milling, cutting and tapping operations on ferrous and non-ferrous metals.

SUPRACUT MQL 45 reduces significantly the oil consumption and has high level biodegradable content.

ADVANTAGES

- Minimum consumption.
- Chlorine and active sulphur free.
- Good anti-wear properties.
- High flash point.
- High viscosity index.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRACUT MQL 45
Aspect	-		Transparent
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur.
- Good dermatological behavior.
- Storage in a frost-free and dry place

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.