



MOTULTECH SUPRAGRIND 10 X

Neat Grinding Oil

DESCRIPTION

SUPRAGRIND 10 X is a neat grinding oil, specially developed for grinding of hard materials of bad machinability as well as gear grinding and sharpening of carbide and HSS tools with diamond or CBN wheels.

APPLICATIONS

SUPRAGRIND 10 X can be used for all types of grinding operations and more specifically for severe grinding operations and gear grinding of bad machinability materials.

Thanks to its properties, **SUPRAGRIND 10 X** is very well adapted for workshops with a fine filtration system (filtration limit 4.5µm).

ADVANTAGES

- Non foaming.
- Good wetting and cooling properties.
- High extreme-pressure power.
- Low consumption.
- High flash point.
- Improve surface finish.
- Prevent the smearing of wheel.

TECHNICAL INFORMATION

| TECHNICAL CHARACTERISTICS | UNITS | METHOD | SUPRAGRIND 10 X |
|---------------------------|-------|--------|--------------------------|
| Density | - | | 842.0 0,842 |
| Storage | - | | in frost-free, dry place |

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free of organo-chlorinated additives
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behaviour

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.