



SUZUKI MARINE 10W-40 M

MINERAL BASE

DESCRIPTION

Semi-synthetic lubricant specially designed for use in SUZUKI Gasoline 4 Stroke outboard engines running under severe conditions, cD120:H120alling for NMMA FC-W lubricants.

APPLICATIONS

STANDARDS API SL

APPROVALS NMMA FC-W under n° FB-13852W

FC-W standard, specially developed for lubricant intended for use in marine engines, is more stringent than requirements for standard marine oils on following points:

- Higher HTHS viscosity at 150°C to ensure better oil film resistance at high temperature and absorb fuel dilution produced during long idling period.
- 40 viscosity grade at hot temperature for severe conditions and warm climates.
- Better shear resistance to maintain lubricant performance at high temperature.
- Outstanding anti-corrosion properties to avoid corrosion due to sea water or salt water fog that can reach combustion chamber through exhaust pipe. Better anti-corrosion performance during wintering periods.
- Keep lubricant original properties even contaminated by sea water.
- Better oxidation resistance.
- Anti-foam properties to avoid foaming and air bubbles introduction into oil circuit.
- Anti-clogging properties to protect oil filters.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.