



## SUZ. MAR. 10W40 M

Lubricant for marine 4 Stroke engines  
Gasoline engines  
Semi-Synthetic

### USO

Semi-synthetic lubricant specially designed for use in SUZUKI Gasoline 4 Stroke outboard engines running under severe conditions, cD120:H120alling for NMMA FC-W lubricants.

### PRESTACIONES

STANDARDS API SL

APPROVALS NMMA FC-W under n° FB-13852W

FC-W standard, specially developed for lubricant intended for use in marine engines, is more stringent than requirements for standard marine oils on following points:

- Higher HTHS viscosity at 150°C to ensure better oil film resistance at high temperature and absorb fuel dilution produced during long idling period.
- 40 viscosity grade at hot temperature for severe conditions and warm climates.
- Better shear resistance to maintain lubricant performance at high temperature.
- Outstanding anti-corrosion properties to avoid corrosion due to sea water or salt water fog that can reach combustion chamber through exhaust pipe. Better anti-corrosion performance during wintering periods.
- Keep lubricant original properties even contaminated by sea water.
- Better oxidation resistance.
- Anti-foam properties to avoid foaming and air bubbles introduction into oil circuit.
- Anti-clogging properties to protect oil filters.

### RECOMENDACIONES

Drain interval: according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral oils.

Nos reservamos el derecho de modificar las características generales de nuestros productos para ofrecer a nuestros clientes el beneficio de los últimos avances tecnológicos. Las especificaciones serán definitivas desde la realización del pedido, sujeto a nuestras condiciones generales de venta y garantía. 02/25

Motul Iberica S.A Sucursal Colombia - Av. Cra 9 #115-06 Of. 905-906, Edificio Tierra Firme - 110111 - Bogota - +57 1 4325359 - +57 1 4325359 -

info@co.motul.com -

motul.com