

**SUZUKI MARINE 4T 10W-30**

**Lubricant for marine 4 stroke engines**  
**Gasoline engines**  
**Semi-Synthetic**

**TYPE OF USE**

Semi-synthetic lubricant specially designed for use in SUZUKI Gasoline 4 stroke outboard engines running under severe conditions, calling for NMMA FC-W lubricants.

**PERFORMANCES****STANDARDS**

API SL

NMMA FC-W under N° FB-84224K

FC-W standard, specially developed for lubricant intended for use in marine engines, is more stringent than requirements for standard marine oils on following points :

- Higher HTHS viscosity @150°C to ensure better oil film resistance at high temperature and absorb fuel dilution produced during long idling period.
- Better shear resistance to maintain lubricant performance at high temperature.
- Outstanding anti-corrosion properties to avoid corrosion due to sea water or salt water fog that can reach combustion chamber through exhaust pipe. Better anti-corrosion performance during wintering periods.
- Keep lubricant original properties even contaminated by sea water.
- Better oxidation resistance.
- Anti-foam properties to avoid foaming and air bubbles introduction into oil circuit.
- Anti-clogging properties to protect oil filters.

**RECOMMENDATIONS**

Drain interval : according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral oils.



## SUZUKI MARINE 4T 10W-30

Lubricant for marine 4 stroke engines  
Gasoline engines  
Semi-Synthetic

### PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 40°C (104°F)	ASTM D445	78.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	12.2 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	150.0
Pour point	ASTM D97	-33.0 °C / -27.4 °F
Flash point	ASTM D92	229.0 °C / 444.2 °F
TBN	ASTM D2896	7.5 mg KOH/g