

SUZUKI MARINE GEAR OIL 90**Lubricant for Outboard Propeller Box
Extreme Pressure****TYPE OF USE**

Gear lubricant specially designed for use in SUZUKI outboard propeller box.

PERFORMANCES

STANDARDS API GL-5

"Extreme Pressure" lubricant for a better wear protection.

SAE 90 viscosity grade at hot temperature to guarantee oil film thickness under severe conditions at high load and high temperature. Help to reduce propeller box noise.

High shear resistance to keep lubricant original performances at high temperature.

High lubricating properties for friction reduction.

Anti-corrosion protection.

Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to SUZUKI's recommendations and tune to your own use.

PROPERTIES

Viscosity grade	SAE J 300	90
Density at 20°C (68°F)	ASTM D1298	0.898
Viscosity at 40°C (104°F)	ASTM D445	186.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	17.0 mm ² /s
Viscosity Index	ASTM D2270	97.0
Pour point	ASTM D97	-25.0 °C / -13.0 °F
Flash point	ASTM D92	203.0 °C / 397.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com