

**Gasoline engine oil
100% Synthetic**

TYPE OF USE

Specifically designed for powerful and recent cars fitted with Gasoline engines, turbocharged or naturally aspirated, direct or indirect injection.

This multipurpose product featuring numerous car maker approvals is especially recommended for vehicles still under warranty.

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, and LPG.

Compatible for catalytic converters.

PERFORMANCES

The BMW Long Life-01 specification imposes severe constraints to the lubricant particularly due to the Valvetronic system. It covers all BMW engines from 2001 to 2004 and also all the previous BMW specifications such as BMW LL-98. From 2004 BMW vehicles require a BMW LL-04 product such as MOTUL Specific LL-04 5W-40, 8100 X-clean 5W-40, 8100 X-clean 5W-30, or 8100 X-clean+ 5W-30.

BMW LL-01 standard covers also all Gasoline engines running only outside European Union countries, Switzerland, Norway and Liechtenstein. Refer to BMW recommendations when in doubt.

The MB 229.5 standard is more stringent than 229.3 in terms of aging and oil film resistance (extended drain interval: on-board computer), detergent / dispersant power (ACEA B4) and requests fuel economy performance: 1.7% fuel economy improvement versus a 15W-40 reference. The specification MB 229.5 applies to all MERCEDES Gasoline engines, including AMG (in 5W-40 viscosity grade) except SLR, and to all MERCEDES Diesel without DPF engines.

The Porsche A40 standard requires extreme high shear resistance from the lubricant. This specification applies to all PORSCHE engines, except Cayenne V6 and Diesel versions (for these specific engines, use an approved Porsche C30 lubricant such as MOTUL 8100 X-clean+ 5W-30).

RENAULT has developed RN0700 and RN0710 standards for oils able to endure the most severe thermal constrains along with modern after treatment systems compatibility.

The Renault RN0700 standard applies to all Naturally Aspirated Gasoline engines (except Renault Sport) of RENAULT Group (Renault, Dacia, Samsung).

The RN0700 specification applies also to all RENAULT Diesel cars fitted with 1.5L dCi engines without DPF (Diesel Particulate Filter) having less than 100 hp output and 20 000 km or 1 year oil drain interval.

The Renault RN0710 standard applies to all turbocharged Gasoline, Renault Sport and Diesel without DPF engines of RENAULT Group (Renault, Dacia, Samsung).

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**Gasoline engine oil
100% Synthetic**

The RN0710 specification does not apply to RENAULT Diesel cars fitted with 1.5L dCi engines without DPF having less than 100 hp output and 20 000 km or 1 year oil drain interval which specifically require a RN0700 lubricant. For the 2,2L dCi with DPF, use only an approved RN0710 lubricant, not a RN0720.

The FIAT 9.55535-H2, M2 and N2 performance levels impose the engine oil to combine both ACEA A3/B4 standard and 5W-40 viscosity grade in order to perfectly lubricate most of the Gasoline and Diesel engines of FIAT, ALFA-ROMEO, and LANCIA produced before July 2007.

PSA B71 2296 standard is suitable for some Gasoline and Diesel engines and requires oils able to endure the most severe thermal constraints in order to provide high thermal stability and avoid black sludge and viscosity increase that soot, coming from combustion residues, may create. The cleanliness of PEUGEOT and CITROËN engines during the whole duration of the drain interval is therefore maintained for longer engine lifetime.

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 20°C (68°F)	ASTM D1298	0.846
Viscosity at 40°C (104°F)	ASTM D445	87.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.1 mm ² /s
Viscosity Index	ASTM D2270	169.0
Pour point	ASTM D97	-35.0 °C / -31.0 °F
Flash point	ASTM D92	231.0 °C / 448.0 °F
TBN	ASTM D2896	10.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**Gasoline engine oil
100% Synthetic**

STANDARDS	
API	SERVICE SN / CF
BMW	LL-01
MERCEDES-BENZ	MB-Approval 229.5
RENAULT	RN0700
VW	502 00 505 00
OE PERFORMANCES	
CITROËN	PSA B71 2296
CITROEN/PEUGEOT	PSA B71 2296
DS (CAPSA)	PSA B71 2296
FIAT	9.55535-H2, 9.55535-M2, 9.55535-N2
PEUGEOT	PSA B71 2296
PORSCHE	A40
RENAULT	RN0710
PRODUCTS	
PSA Groupe	PSA B71 2296

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

