



TECH GREASE FG2

Premium Multipurpose Grease
Mineral White Oil - Vaseline Codex

TYPE OF USE

TECH GREASE FG 2 is a multi-purpose grease which is permitted to come into accidental contact with food.

PERFORMANCES

STANDARDS FDA - CFR 178.3570 Meets the requirements.
 NSF H1 Registration number 139436.

Lubrication of antifriction bearings, chains, joints, slides in Food processing, Cosmetic and Pharmaceutical industries.

TECH GREASE FG 2 is certified NSF H1. Registration number 139436.

TECH GREASE FG 2 meets the FDA - 21 CFR 178.3570 specifications and can be used in mechanical systems where direct contact with the lubricant cannot be avoided.

PROPERTIES

Color	Visual	Translucent
Density at 20°C (68°F)	ISO 3675	0.900 kg/L
Drop point	ISO 2176	Not applicable °C
NLGI Grade		2
Thickener		Inorganic
Penetration 60 strokes	ISO 2137	265-295 1/10 mm
Temperature range		-20 to 180 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com