

TEKMA NORMA 10W

Lubricant for hydraulic systems and hydrostatic transmissions
Viscosity: SAE 10W monograde

TYPE OF USE

Suitable for hydraulic systems, torque converters and mechanical transmissions when an engine oil is recommended by manufacturers.

PERFORMANCES

STANDARDS API CF / SF

PERFORMANCES CATERPILLAR Zinc content > 900 ppm as required by CATERPILLAR for hydraulic systems.

Ensures engine protection and life time owing to piston groove deposits reduction.
 High dispersant level : reduce soot build up and oil filter plugging risk.
 Excellent bore polishing protection.
 Anti-oxydation, Anti-corrosion, Anti-rust, Anti-foam.

RECOMMENDATIONS

Drain interval : refer to manufacturers' recommendations and tune to your own use.
 Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 40°C (104°F)	ASTM D445	30.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	5.2 mm ² /s
Viscosity Index	ASTM D2270	103.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



TEKMA NORMA 10W

Lubricant for hydraulic systems and hydrostatic transmissions
Viscosity: SAE 10W monograde

Pour point	ASTM D97	-36.0 °C / -33.0 °F
Flash point	ASTM D92	226.0 °C / 439.0 °F
TBN	ASTM D2896	10.1 mg KOH/g