



MOTUL TEKMA POWER X 10W-30

**Dedicated genset oil
Synthetic Technology**

TYPE OF USE

TEKMA POWER X 10W-30 is a 4-stroke diesel and petrol engine oil specially developed for gensets running with low sulfur fuel (≤ 50 ppm).

TEKMA POWER X 10W-30 formulation reinforced with synthetic base stocks provides outstanding resistance to oxidation, easier flowing at cold temperature and longer oil lifetime. Viscosity grade at cold temperature minimizes wear when engine start up and save fuel compare to a standard viscosity 15W-40.

TEKMA POWER X 10W-30 is approved for use in Champion gensets.

PERFORMANCES

STANDARDS	ACEA E7/E9
	API CK-4/SN

TEKMA POWER X 10W-30 meets or exceeds the most common specifications and OEM requirements:

- HONDA
- CRUSADER
- MERCUISER
- VOLVO PENTA
- YAMAHA

TEKMA POWER X 10W-30 is suitable for 4-stroke engines powered by Gasoline or Diesel, naturally aspirated or turbo-charged, indirect or direct injection.

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

motul.com



MOTUL TEKMA POWER X 10W-30

Dedicated genset oil
Synthetic Technology

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)		0.866
	ASTM D445	83.7 cSt
Viscosity at 40°C (104°F)		
	ASTM D445	11.8 cSt
Viscosity at 100°C (212°F)		
	ASTM D97	-40.0 °C / -40.0 °F
Pour point		
Sulfated Ash	ASTM D874	
		% weight
		1.00
TBN	ASTM D2896	9.8 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24