



TEKMA POWER X 10W30

Technosynthese®

DESCRIPTION

TEKMA POWER X 10W-30 is a 4-stroke diesel and petrol engine oil specially developed for gensets running with low sulfur fuel (≤ 50 ppm). TEKMA POWER X 10W-30 formulation reinforced with synthetic base stocks provides outstanding resistance to oxidation, easier flowing at cold temperature and longer oil lifetime. Viscosity grade at cold temperature minimizes wear when engine start up and save fuel compare to a standard viscosity 15W-40. TEKMA POWER X 10W-30 is approved for use in Champion gensets.

ADVANTAGES

- Protection against soot build-up
- Optimized drain interval and lifecycle cost
- Piston groove deposit control
- Low maintenance costs

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	TEKMA POWER X 10W30
Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.866
Viscosity at 40°C (104°F)	ASTM D445	83.7 cSt
Viscosity at 100°C (212°F)	ASTM D445	11.8 cSt
Pour point	ASTM D97	-40.0 °C / -40.0 °F
Sulfated Ash	ASTM D874	1.00 % weight
TBN	ASTM D2896	9.8 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F



STANDARDS / APPROVALS / PERFORMANCE LEVEL

TEKMA POWER X 10W30 meets the following standards:

- ACEA - E7/E9
- API - CK-4/SN

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.