



TEKMA POWER X 10W30

Dedicated genset oil

CONSEILS D'UTILISATIONS

TEKMA POWER X 10W-30 is a 4-stroke diesel and petrol engine oil specially developed for gensets running with low sulfur fuel (≤ 50 ppm).

TEKMA POWER X 10W-30 formulation reinforced with synthetic base stocks provides outstanding resistance to oxidation, easier flowing at cold temperature and longer oil lifetime. Viscosity grade at cold temperature minimizes wear when engine start up and save fuel compare to a standard viscosity 15W-40.

TEKMA POWER X 10W-30 is approved for use in Champion gensets.

PERFORMANCES

NORMES

ACEA E7/E9

API CK-4/SN

TEKMA POWER X 10W-30 meets or exceeds the most common specifications and OEM requirements:

- HONDA
- CRUSADER
- MERCUISER
- VOLVO PENTA
- YAMAHA

TEKMA POWER X 10W-30 is suitable for 4-stroke engines powered by Gasoline or Diesel, naturally aspirated or turbo-charged, indirect or direct injection.

RECOMMANDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.



TEKMA POWER X 10W30

Dedicated genset oil

PROPRIÉTÉS

Grade de viscosité	SAE J 300	10W-30
Densité à 20°C		0.866
Viscosité à 40°C (104°F)	ASTM D445	83.7 cSt
Viscosité à 100°C (212°F)	ASTM D445	11.8 cSt
Point d'écoulement	ASTM D97	-40.0 °C / -40.0 °F
Cendres sulfatées	ASTM D874	% masse 1.00
TBN	ASTM D2896	9.8 mg KOH/g
Point éclair	ASTM D92	224.0 °C / 435.0 °F