



MOTULTECH THERMIC EVO 420

Quenching Oil

DESCRIPTION

THERMIC EVO 420 is an accelerated quenching oil formulated from highly refined base oils. Its use is more comfortable as it respects more the users.

THERMIC EVO 420 is especially adapted for heat treatment under vacuum and can also be used in BATCH furnace type.

APPLICATIONS

THERMIC EVO 420 is particularly adapted for carbon steels and alloyed steels quenching under vacuum.

THERMIC EVO 420 was developed to answer the requirements of the automotive industry.

ADVANTAGES

- Use temperature: 40-90°C (maximum 130°C)
- Minimum loss on parts thanks to its fluidity
- Reduce deformation and crack risks
- Excellent resistance to oxidation
- Reduces fire risks due to its high flash point

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	THERMIC EVO 420
Density	-		841.0 0,841
Self-Ignition Point	°C	ASTM D92	260.0

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free of organo-chlorinated additives and formaldehyde releaser
- High flash point
- Good dermatological behaviour
- Storage in a frost-free and dry place



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.