



## THERMIC FGP

Heat Treatment - Mass quenching

### DESCRIPTION

**THERMIC FGP** is a synthetic soluble oil used diluted in water for mass quenching. Free of nitrite, it allows to obtain, according to the concentration in use, of accelerated cooling rates between water and oil.

### APPLICATIONS

**THERMIC FGP**, usually used after mass heating, can be diluted between 10% and 25%, according to the grade of steels to treat. The recommended temperature of the tank is between 25°C and 45°C.

### ADVANTAGES

- Avoids risk of fire and reduces smoke emissions.
- Reduces manufacturing costs.
- Low use concentration.
- Low consumption.
- Good performance in time.
- Cleanliness of parts after quenching and corrosion protection.
- Specific formulation to reduce the risk of quenching cracks.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	THERMIC FGP
Aspect	-		Clear
Density	-		1,020.0 1,020
pH	-	NFT 60.193	9.6 Diluted at 15%, at 23°C
Refractometer Factor	-		2.9 (Reading in ° Brix at 18 % at 23°C)

These characteristics are given only for information and can be updated over time.



## INSTRUCTIONS

Periodically check the concentration of the product in use, using a refractometer and comply with the attached curve. It is recommended to store the products in temperate conditions in sealed containers.

## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.