



MOTULTECH THERMIC SH 615

Heat Treatment

DESCRIPTION

THERMIC SH 615 is a soluble quenching polymer, which is nitrite, DEA, formaldehyde free. It has adjustable cooling speeds, managed with dilution ratios in order to cover a wide range of applications. It can also be used for tempering stop under specific conditions.

APPLICATIONS

THERMIC SH 615 has been specially designed for superficial quenching and heating by induction or conduction. The concentration to use depends on the nature of the steel you wish to quench, and the quenching depth.

Generally, concentration of **THERMIC SH615** is between 6 and 15% (shower, dipping...). The advised temperature of bath is between 30 and 50°C maximum. **THERMIC SH 615** can also be used for tempering stop from 4% concentration.

ADVANTAGES

- **THERMIC SH 615** is very cost effective thanks to low concentration and reduced product consumption (loss on chips and parts is limited).
- Few residues on parts.
- Easy filtration of baths (no clogging of filters).
- **THERMIC SH 615** gives short term corrosion protection of quenched parts which avoid the use of an additional product for temporary protection.
- Very good dermatological behavior.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	THERMIC SH 615
Aspect	-		Limpide
Density	-		1,050.0 1,050
pH	-	NFT 60 193	9.2 (Diluted at 10%, at 23°C)
Refractometer Factor	-		2.5

These characteristics are given only for information and can be updated over time.



INSTRUCTIONS

Periodically check the concentration of the product in use, using a refractometer and comply with the attached curve. It is recommended to store the products in temperate conditions in sealed containers.

THERMIC SH 615 concentration must be checked regularly with a refractometer and must be adjusted in accordance with the graph below, correction coefficient 2.5. In case of a long pause of the machine (end of the week for example), it is necessary to adjust the concentration at the upper limit value.

Installation must be cleaned regularly (especially the showers), do not leave saturated filtration media in contact with the fluid during production pauses. It is recommended to store products in a tempered warehouse and in closed drums. Expiration date: in storage conditions defined above in initial sealed packaging.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.