



MOTUL TIMBER 120

Chainsaw chain lubricant
Adhesive formula
Manual or Automatic lubrication system
Mineral

TYPE OF USE

Specially formulated for chainsaws chain lubrication.
All types of chainsaws, thermal and electric, with manual or automatic chain lubrication systems.

PERFORMANCES

Appropriate viscosity for an efficient lubrication while preventing oil splatters.
Strong, stringy lubricant. Excellent adhesion.
Fluid enough but highly adhesive.
Reduced oil consumption.
Minimized heating.
Increased protection of chain and guide.
Extended chain and guide bar life duration.
Anti-oxidation and anti-rust properties.
Anti-corrosion and anti-wear protection.

RECOMMENDATIONS

Reduction of oil consumption.
Reduction of heating.
Better protection for a lasting quality of the chains.

PROPERTIES

Density at 20°C (68°F)	ASTM D1298	0.858
Viscosity at 40°C (104°F)	ASTM D445	119.8 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	18.6 mm ² /s
Pour point	ASTM D97	-42.0 °C / -44.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

03/26



MOTUL TIMBER 120

Chainsaw chain lubricant
Adhesive formula
Manual or Automatic lubrication system
Mineral

Flash point

ASTM D92

227.0 °C / 441.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



MOTUL TIMBER 120

Chainsaw chain lubricant
Adhesive formula
Manual or Automatic lubrication system
Mineral

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com