

MOTUL TRANSLUBE POWER 75W-90

100% SYNTHETIC BASE

DESCRIPTION

High Performance anti-emulsion gear oil specially formulated to lubricate outboard big engine high loaded propeller boxes :
EVINRUDE, FORCE, JOHNSON, MARIMER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU, YAMAHA,...etc.

Specially developed for outboard big engine propeller boxes operating under shocks, heavy loads and low revolution speed, or moderate loads and high revolution speed.
Suitable also for all transmissions systems using gears, bevel gears, stepdown gears,...etc.

APPLICATIONS

100% Synthetic "Extreme Pressure" lubricant for efficient anti-wear protection, better resistance at high temperature and extended life time.

Formula reinforced with Ester to increase oil film resistance even in the most extreme conditions.

Very high lubricating properties to reduce friction and wear.

Viscosity grade 90 at high temperature to provide outstanding oil film resistance at high temperature and high load, and to reduce transmission noise.

Anti-corrosion, Anti-foam.

High anti-emulsion properties.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.