

**TRANSMISSION FLUID A****Automatic gearbox lubricant  
ATF TYPE A****TYPE OF USE**

For all systems where GENERAL MOTORS ATF type A standard is required.  
Automatic gearboxes and transmissions, torque converters, power steering systems, hydraulic systems...  
If GM-DEXRON II standard is recommended, use MOTUL DEXRON II D.

**PERFORMANCES****PERFORMANCES**                      GENERAL MOTORS ATF Type A

Very high fluidity under low temperatures which allows gear change very easy.  
Thermal stability under high temperature.  
Anti-wear, Anti-corrosion, Anti-foam.

**RECOMMENDATIONS**

Oil change: According to manufacturers' requirements and adjust according to your own use.

**PROPERTIES**

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.878
Viscosity at 40°C (104°F)	ASTM D445	40.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	7.0 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	157.0
Pour point	ASTM D97	-45.0 °C / -49.0 °F
Flash point	ASTM D92	210.0 °C / 412.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com