

2-Stroke Scooter Engine Lubricant
Premix or injector systems
Technosynthese®

TYPE OF USE

Tribal Scoot Plus 2T is designed for all scooters used in daily urban commuting.

Suitable for both direct injection and conventional carbureted 2-stroke engines, it can be used with oil injection systems or as a premix. Fully compatible with catalytic converters.

PERFORMANCES

STANDARDS

API TC

JASO FC

This Technosynthese® engine oil is engineered for scooters operating at high RPM, providing excellent oil film strength for superior wear protection.

Its low-smoke formulation minimizes exhaust emissions, prevents deposits, and maintains cleanliness throughout the engine – from the combustion chamber and spark plug to the piston crown, ring grooves, exhaust port, and exhaust pipe.

RECOMMENDATIONS

Mixing ratio: 2% to 4% (50:1 to 25:1) according to manufacturer specifications.

Adjust the ratio based on your specific use and operating conditions.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.861
Viscosity at 40°C (104°F)	ASTM D445	71 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	10 mm²/s
Viscosity Index	ASTM D2270	126
Pour point	ASTM D97	-34 °C / -29 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



TRIBAL SCOOT PLUS 2T

2-Stroke Scooter Engine Lubricant
Premix or injector systems
Technosynthese®

TBN

ASTM D2896

2 mg KOH/g

Flash point

ASTM D92

118 °C / 244 °F