



MOTUL TRUCK+ 15W-40

**Multi-Fleet Lubricant for Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines
Diesel and Petrol engines naturally aspirated or Turbocharged
Mineral**

TYPE OF USE

TRUCK+ LCV 15W-40 is a multi-Fleet Lubricant for Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines.

PERFORMANCES

Motul TRUCK+ LCV 15W-40 is a mixed fleet diesel engine oil designed to provide excellent protection for fleets containing pickups, minibuses, LCV's and heavy duty engines from a variety of manufacturers. Suitable as single lubricant in case of fleet composed of new & old generation engines on Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines thus allowing the stock of lubricants to be reduced.

Motul TRUCK+ LCV 15W-40 is a versatile product which can be used in trucks, buses, LCVs, off-road vehicles and equipment, and also in agricultural vehicles.

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)		0.872
Viscosity at 40°C (104°F)	ASTM D445	104.3 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm²/s
Viscosity Index	ASTM D2270	141.0
Pour point	ASTM D97	-39.0 °C / -38.2 °F
TBN	ASTM D2896	10.5 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL TRUCK+ 15W-40

**Multi-Fleet Lubricant for Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines
Diesel and Petrol engines naturally aspirated or Turbocharged
Mineral**

Flash point

ASTM D92

229.0 °C / 444.2 °F



MOTUL TRUCK+ 15W-40

**Multi-Fleet Lubricant for Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines
Diesel and Petrol engines naturally aspirated or Turbocharged
Mineral**

STANDARDS	
ACEA	E7 (Replaces E5 and E3)
API	CI-4/SL (backwards compatible to API CH-4)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

