



## MOTULTECH UNIVERSELLE 150 SC

Metal cold heading

### DESCRIPTION

**UNIVERSELLE 150 SC** is a multi-purpose oil, free of organo-chlorinated additives, suitable for cold forming, tapping and lubrication of machine tool parts.

### APPLICATIONS

**UNIVERSELLE 150 SC** is recommended for the lubrication of machine-tools especially when **UNIVERSELLE** range is used for cold heading operations. It avoids the fast decline of performance of the forming oil due to accidental leakages.

**UNIVERSELLE 150 SC** is suitable for the cold heading operations when a very good lubrication is requested.

**UNIVERSELLE 150 SC** is compatible with all metals.

### ADVANTAGES

- Compatible with all metals.
- High lubricating properties.
- High Extreme Pressure properties.
- Accidental leakage of **UNIVERSELLE 150 SC** into the cold heading circuit does not affect the properties and the performances of the heading fluid.
- Les fuites accidentelles de ce type de fluide de graissage dans le circuit de frappe à froid n'altèrent pas les propriétés du fluide de frappe


### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	UNIVERSELLE 150 SC
Aspect	-		Transparent
Density	-		899.0 0,899
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

### HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur
- Good dermatological behaviour
- Storage in a frost-free and dry place



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.