



## UNIVERSELLE 90 SC

Cold heading

Mineral base oil

### DESCRIPTION

**UNIVERSELLE 90 SC** is multi-purpose oil, free of organo-chlorinated additives, suitable for cold deformation, tapping and lubrication of machine tool parts.

### APPLICATIONS

**UNIVERSELLE 90 SC** is suitable for :

- Cold forming to obtain elongated parts (extreme pressure properties)
- Machine-tools lubrication (anti-wear property)
- Tapping by cutting or by deformation
- Rolling and threading by deformation
- Horizontal and vertical presses

### ADVANTAGES

- Compatible with all kinds of metals.
- Can be used for cold forging and machine-tool lubrication.
- High wettability, ensuring even distribution of the lubricant on both the tool and machining part.
- High oxidation stability even at high speeds.
- Good separation from wire drawing soaps.
- Less smoke.
- No scrubbing of machine-tools parts.


### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	UNIVERSELLE 90 SC
Aspect	-		Transparent
Density	-		895.0 0,895
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

### HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur
- Good dermatological behaviour
- Storage in a frost-free and dry place



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.