



UNIVERSELLE 90 SC

Metal cold heading

DESCRIPTION

UNIVERSELLE 90 SC is multi-purpose oil, free of organo-chlorinated additives, suitable for cold deformation, tapping and lubrication of machine tool parts.

APPLICATIONS

UNIVERSELLE 90 SC is suitable for :

- Cold forming to obtain elongated parts (extreme pressure properties)
- Machine-tools lubrication (anti-wear property)
- Tapping by cutting or by deformation
- Rolling and threading by deformation
- Horizontal and vertical presses

ADVANTAGES

- Compatible with all kinds of metals.
- Can be used for cold forging and machine-tool lubrication.
- High wettability, ensuring even distribution of the lubricant on both the tool and machining part.
- High oxidation stability even at high speeds.
- Good separation from wire drawing soaps.
- Less smoke.
- No scrubbing of machine-tools parts.


TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	UNIVERSELLE 90 SC
Aspect	-		Transparent
Density	-		895.0 0,895
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Free from organo-chlorinated additives and active sulphur
- Good dermatological behaviour
- Storage in a frost-free and dry place



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.