

**URBAN SCOOT MAX 4T 5W-40**

**4 stroke engine oil Scooter and Maxi Scooter  
100% Synthetic**

**TYPE OF USE**

Specifically designed for scooters and maxi-scooters fitted with 4 stroke engines, injection or carburator, with or without catalytic converters.

All scooters used for daily commuting or downtown in the city.

Suitable for leaded or unleaded fuel.

**PERFORMANCES**

STANDARDS                      API SJ  
                                            JASO MA Level

100% synthetic oil, reduces engine internal friction, improves mechanical efficiency.

Excellent high temperature resistance particularly indicated for city use.

The SAE 5W-40 viscosity grade corresponds to the most recent manufacturers' recommendations and improves friction and engine starts in cold conditions.

Low volatility to reduce oil consumption.

Ensure engine cleanliness, high detergent and dispersives properties and resistance at viscosity increase due to unburned deposits produced by the engine. Ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

**RECOMMENDATIONS**

Drain interval : refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

**PROPERTIES**

Viscosity grade	SAE J 300	5W-40
-----------------	-----------	-------

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**URBAN SCOOT MAX 4T 5W-40****4 stroke engine oil Scooter and Maxi Scooter  
100% Synthetic**

Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	84.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.3 mm <sup>2</sup> /s
Pour point	ASTM D97	-33.0 °C / -27.4 °F
Flash point	ASTM D92	230.0 °C / 446.0 °F
TBN	ASTM D2896	10.2 mg KOH/g