

**URBAN SCOOT PLUS 4T 10W-40****4 stroke engine oil Scooter  
Technosynthese®****TYPE OF USE**

Specifically designed for scooters fitted with 4 Stroke engines, injection or carburetor, with or without catalytic converters.  
All scooters used downtown in the city.

**PERFORMANCES**

STANDARDS                      API SJ  
    JASO MA Level

Technosynthese® oil, reinforced with a synthetic base stock which provides high protection.

Anti-wear formulation to increase engine lifetime.

Excellent high temperature resistance particularly indicated for city use.

The SAE 10W-40 viscosity grade corresponds to the most recent manufacturers' recommendations.

Ensure engine cleanliness, detergent and dispersive properties and resistance at viscosity increase due to unburned deposits produced by the engine. Ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

**RECOMMENDATIONS**

Drain interval : according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

**PROPERTIES**

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.869
Viscosity at 40°C (104°F)	ASTM D445	100.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm <sup>2</sup> /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## URBAN SCOOT PLUS 4T 10W-40

**4 stroke engine oil Scooter  
Technosynthese®**

Viscosity Index	ASTM D2270	153.0
Pour point	ASTM D97	-27.0 °C / -16.6 °F
Flash point	ASTM D92	228.0 °C / 442.4 °F
TBN	ASTM D2896	8.3 mg KOH/g